



Stainless steel chains for hoists

Measures DIN 5684-5 / EN 818-7,

Tested, with test certificate

Material: 1.4310, 1.4404, 1.4571, 1.4828, 1.4841

Surface: grid blasted / polished

Lengths on desire

aRö Stainless
lift

Measures DIN 5684-5, Grade 50

Wire-Ø x Pitch [mm]	Inside width b1 min. [mm]	Outside width b2 max. [mm]	Lifting capacity [kg]	Weight ca. [kg/m]
4 x 12	4,8	13,6	320	0,35
5 x 15	6	17	500	0,54
6 x 18	7,2	20,4	750	0,8
7 x 21	8,4	23,8	1.000	1,1
8 x 24	9,6	27,2	1.250	1,4
9 x 27	10,8	30,6	1.600	1,8
10 x 28	12	34	2.000	2,2
11 x 31	13,2	37,4	2.500	2,7
13 x 36	15,6	44,2	3.350	3,7

Measures EN 818-7, fine tolerance, Grade P

4 x 12	4,8	13,6	320	0,35
5 x 15	6	17	500	0,54
6 x 18	7,2	20,4	750	0,8
7 x 21	8,4	23,8	1.000	1,1
8 x 24	9,6	27,2	1.250	1,4
9 x 27	10,8	30,6	1.600	1,8
10 x 30	12	34	2.000	2,2
11 x 33	13,2	37,4	2.500	2,7
13 x 39	15,6	44,2	3.350	3,7

Other measures on request!

Technical changes subject to alterations. All specifications without engagement.