



Stainless Steel Conveyor Chains Grade 60



- Materials:
1.4301, 1.4310, 1.4404, 1.4462, 1.4571, 1.4828, 1.4841
- Surface blasted or polished; further types on request
- Test certificate EN 10204-3.1
- Lengths and surfaces at buyer's option

size d [mm]	pitch t [mm]	Inside width min. b1 [mm]	Outside width max. b2 [mm]	Weight app. [kg / m]	Tensile force Grade 60 max. [t]	Breaking force min. [kN]
6	27,5	8,8	21,2	0,68	0,90	35
6	32	8,8	21,5	0,65	0,90	35
8	25,4	9,6	26,0	1,30	1,60	62
8	31	10,4	28,0	1,25	1,60	62
8	38	13,5	29,8	1,20	1,60	62
9	27	12,5	31,8	1,75	2,00	78
9	28	11,2	31,3	1,73	2,00	78
9	31	16,2	43,2	1,63	2,00	78
10	31	12,5	34,0	2,12	2,50	98
10	35	12,5	36,0	2,05	2,50	98
10	38	12,5	34,0	2,00	2,50	98
11	31	13,8	37,4	2,70	3,00	117
11	35	13,8	37,4	2,60	3,00	117
13	36	15,6	47,0	3,80	4,25	166
13	45	16,3	47,0	3,50	4,25	166
13	65	18,2	46,8	3,10	4,25	166

Other materials and measures on request.

Sprocket wheels, deflection rollers etc.: See separate brochure under „sprocket wheels“

Technical changes subject to alterations. All specifications without engagement.